

BIGHAM

MECHANICAL TRIP PARATILL

Model 303

Mechanical Trip 3 Leg Paratill



Standard Features

Tool Bar Heavy duty diamond mast frame has 4" x 7" x 3/8" rectangular tube

Legs Mechanical trip paratill leg is angled 45 degrees to the side at working depth of 12" to 17"

3 Point Hitch Category II & III Standard on 3 Leg

3 Point hitch Category III Standard on 4 Leg

Wide 4" drop hitch is standard on all models

Coulter Assembly 20" duraflute blade front of each leg with up to 900 pounds of residue slicing pressure

Gauge Wheels 20.5 - 8.0 x 10 load range E tires on 6 bolt hubs & 2" spindles

Horsepower requirements are 30-40 DBHP per leg depending on soil type, condition and operating depth and tractor type (rubber tire, rubber track or steel track).

Prices and specifications subject to change without notice.

Model

907-303

907-304T

Approx DBHP

120

160

Approx Weight

2800 lbs

3600 lbs

Selling Price



Model 304T

Mechanical Trip 4 Leg Paratill



Sold and Serviced by:



KELLOUGH'S

#3 7491-49 Ave.
Red Deer, Alberta T4P 1N1
Ph: (403) 347-2646
Toll Free: 1-888-500-2646
Fax: (403) 347-2656
www.kelloughenterprises.com